

Irish Fencing Services

SECURE • ENHANCE • PROTECT

www.irishfencing.com

Q40 Fencing

To be read with preliminaries / General Conditions

Fencing Systems

- Manufacturer: Irish Fencing Services
- Product Reference: Irfen® Solid Roundbar Railing
- Drawing No: C0100
- Height: 900,1200,1500,1800,2100,2400mm
- Standard: To BS1722-9
- Panel: Constructed using either 12, 16, or 20mm solid round bars at maximum 100mm gap
- Rails: 2 no horizontal flat rails either 30 x 10, 40 x 10 or 50 x 10 punched for each infill. Bars welded at each punched hole
- Posts: 50 x 50, 60 x 60 or 80 x 40mm hot dipped galvanised post to BS EN9 ISO 1461:2009 after fabrication and subsequently electrostatically powder coated in a plant complying to EN 1722Part 16
- Post Centres: 900-1800mm High 2750mm
 - 2100mm High- 2500mm
 - 2400mm High 2250mm
- Fixings: Irfen® angle cleats and 10mm Irfen® anti vandal bolts and nuts
- Method of setting posts: Erect posts plumb and level in 25n concrete bases minimum size 350 x 350 x 600mm or as recommended by supplier, set 100mm below ground level
- Accessories: None
- Conformity: Submit manufacturers and installer certificates to BS 1722-9









